

AUG 27 2007

33890US01  
10/800,471  
Art Unit: 1764**LISTING OF THE CLAIMS**

1. (Currently Amended) A process to inhibit or limit the decomposition of a halide-containing olefin oligomerization catalyst system during recovery of an olefin oligomerization product comprising the steps of:
  - a) forming an intermediate stream by contacting an olefin oligomerization reactor effluent stream which comprises olefin product(s), catalyst system, and heavies with an alcohol that is soluble in any portion of the reactor effluent stream; and
  - b) separating the intermediate stream of step (a) into at least one product stream comprising the olefin oligomerization product and at least one heavies stream;  
wherein the separation comprises a distillation comprising a reboiler and material passed through the reboiler is maintained below about 190 °C. and  
wherein the catalyst system comprises a chromium source, a pyrrole-containing compound and an alkylaluminum compound and wherein the alcohol is added in an amount to effect a mole alcohol to mole aluminum ratio between about 2.5 and about 1.5.
2. (Canceled)
3. (Original) The process of claim 1 wherein the reactor effluent stream comprises olefin product(s); an olefin oligomerization catalyst system; an organic diluent; one or more mono-olefins; and polymer.
4. (Original) The process of claim 1 wherein the alcohol has a boiling point different from the olefin product in the reactor effluent stream.
5. (Original) The process of claim 1 wherein the alcohol has 6 or more carbon atoms per molecule.
6. (Original) The process of claim 1 wherein the olefin oligomerization catalyst system comprises a halogenated alkylaluminum compound.
- 7-9 Canceled

33890US01  
10/800,471  
Art Unit: 1764

10. (Currently Amended) The process of claim ~~[[7]]~~ 1 ~~wherein the distillation comprises a reboiler and~~ wherein material passed through the reboiler is maintained below about 175°C.
11. (Original) The process of claim 1 wherein the alcohol is selected from the group of 1-hexanol, 3-hexanol, 2-ethyl-1-hexanol, 3-octanol, 1-heptanol, 2-heptanol, 3-heptanol, 4-heptanol, 2-methyl-3-heptanol, 1-octanol, 2-octanol, 4-octanol, 7-methyl-2-decanol, 1-decanol, 2-decanol, 3-decanol, 4-decanol, 5-decanol, 2-ethyl-1-decanol, and mixtures thereof.
12. (Original) The process of claim 1 wherein the alcohol is selected from the group of diols and polyols.
13. (Currently Amended) The process of claim ~~[[7]]~~ 1 wherein the distillation process includes at least two distillation stages.
14. (Original) The process of claim 1 wherein the alcohol has been treated to minimize water content.
15. (Currently Amended) The process of claim 1 further comprising ~~the~~ a step of minimizing water content of the alcohol before step (a).
16. (Original) The process of claim 15 wherein the step of minimizing the water content of the alcohol comprises contacting the alcohol with an adsorbent capable of adsorbing water.
17. (Currently Amended) The process of claim ~~[[2]]~~ 1 wherein the olefin oligomerization product comprises one or more olefin trimers.
18. (Currently Amended) A process to inhibit or limit the decomposition of a halide-containing olefin oligomerization catalyst system during recovery of ~~the~~ an olefin oligomerization product comprising the steps of:
  - a) minimizing water content in an alcohol; ~~and~~
  - b) forming an intermediate stream by contacting an olefin oligomerization reactor effluent stream which comprises olefin product(s), catalyst system, and heavies with the alcohol; and
  - c) separating the intermediate stream of step (b) into at least one olefin oligomerization product stream and at least one heavies stream;

33890US01  
10/800,471  
Art Unit: 1764

wherein the separation comprises a distillation comprising a reboiler and material passed through the reboiler is maintained below about 190 °C, and

wherein said catalyst system comprises a chromium source, a pyrrole-containing compound and an alkylaluminum compound and wherein the alcohol is soluble in any portion of the reactor effluent stream.

19. (Canceled)
20. (Currently Amended) A process according to claim 18 wherein said reactor effluent stream comprises olefin product(s); ~~an~~ the olefin oligomerization catalyst system; an organic diluent; one or more mono-olefins; and heavies.
21. (Original) A process according to claim 18 wherein the olefin oligomerization catalyst system comprises a halide compound and an alkylaluminum compound.
22. (Original) A process according to claim 1 wherein the olefin oligomerization catalyst system comprises a halide compound and a metal alkyl compound.
23. (Original) A process according to claim 1 wherein the olefin oligomerization catalyst system comprises a mixture of an alkylaluminum compound and a halogenated alkylaluminum compound.
24. (Original) A process according to claim 18 wherein the olefin oligomerization catalyst system comprises a halogenated alkylaluminum compound.
25. (Original) A process according to claim 18 wherein the olefin oligomerization catalyst system comprises a mixture of an alkylaluminum compound and a halogenated alkylaluminum compound.
26. (Currently Amended) The process of claim ~~[[22]]~~ 6 wherein the halogenated alkylaluminum compound is diethylaluminum chloride.
27. (Original) The process of claim 24 wherein the halogenated alkylaluminum compound is diethylaluminum chloride.

33890US01  
10/800,471  
Art Unit: 1764

28. (Original) The process of claim 18 wherein the alcohol has a boiling point different from the olefin product in the reactor effluent stream.
29. (Currently Amended) The process of claim ~~[[28]]~~ 18 wherein the alcohol has 6 or more carbon atoms per molecule.
30. (Original) The process of claim 18 wherein the alcohol is selected from the group of 1-hexanol, 3-hexanol, 2-ethyl-1-hexanol, 3-octanol, 1-heptanol, 2-heptanol, 3-heptanol, 4-heptanol, 2-methyl-3-heptanol, 1-octanol, 2-octanol, 4-octanol, 7-methyl-2-decanol, 1-decanol, 2-decanol, 3-decanol, 4-decanol, 5-decanol, 2-ethyl-1-decanol, and mixtures thereof.
31. (Original) The process of claim 18 wherein the alcohol is selected from the group of diols and polyols.
- 32-34 (Canceled)
35. (Currently Amended) The process of claim ~~[[32]]~~ 18 ~~wherein the distillation comprises a reboiler and~~ wherein material passed through the reboiler is maintained below 175°C.
36. (Currently Amended) The process of claim ~~[[32]]~~ 18 wherein the distillation process includes at least two distillation stages.
37. (Currently Amended) A process to inhibit or limit the decomposition of a halide-containing olefin oligomerization catalyst system during recovery of ~~the an olefin~~ an olefin oligomerization product comprising the steps of:
- a) forming an intermediate stream by contacting an olefin oligomerization reactor effluent stream which comprises olefin product(s) and catalyst system with an alcohol that is soluble in any portion of the reactor effluent stream; and
  - b) separating the intermediate stream of step (a) into at least one olefin oligomerization product stream;
- ~~wherein the temperature of step (b) is less than or equal to 200°C wherein the separation of step (b) comprises a distillation comprising a reboiler and material passed through the reboiler is maintained below about 190°C.~~

33890US01  
10/800,471  
Art Unit: 1764

38. (Canceled)
39. (Currently Amended) The process of claim 37 ~~wherein the temperature of step (b) is less than or equal to~~ wherein material passed through the reboiler is maintained below about 175°C.
40. (Canceled)
41. (Currently Amended) The process of claim ~~[[40]]~~ 37 wherein the distillation includes at least two distillation stages.
42. (Currently Amended) The process of claim 37 wherein the reactor effluent stream comprises olefin product(s); ~~an~~ the olefin oligomerization catalyst system; an organic diluent; and one or more mono-olefins.
43. (Original) The process of claim 37 wherein the alcohol has a boiling point different from the olefin product in the reactor effluent stream.
44. (Original) The process of claim 37 wherein the alcohol has 6 or more carbon atoms per molecule.
45. (Original) The process of claim 37 wherein the alcohol is selected from the group of 1-hexanol, 3-hexanol, 2-ethyl-1-hexanol, 3-octanol, 1-heptanol, 2-heptanol, 3-heptanol, 4-heptanol, 2-methyl-3-heptanol, 1-octanol, 2-octanol, 4-octanol, 7-methyl-2-decanol, 1-decanol, 2-decanol, 3-decanol, 4-decanol, 5-decanol, 2-ethyl-1-decanol, and mixtures thereof.
46. (Original) The process of claim 37 wherein the alcohol is selected from the group of diols and polyols.
47. (Original) The process of claim 37 wherein the alcohol has been treated to minimize water content.
48. (Currently Amended) The process of claim 37 further comprising ~~the~~ a step of minimizing water content in the alcohol before step (a).
49. (Original) The process of claim 48 wherein the step of minimizing the water content of the alcohol comprises contacting the alcohol with an adsorbent capable of adsorbing water.

33890US01  
10/800,471  
Art Unit: 1764

50. (Original) The process of claim 1 wherein the alkylaluminum compound is a mixture of triethylaluminum and diethyl aluminum chloride, the alcohol is 2-ethyl-1-hexanol, and the olefin product comprises 1-hexene.
51. (Original) The process of claim 18 wherein the alkylaluminum compound is a mixture of triethylaluminum and diethyl aluminum chloride, the alcohol is 2-ethyl-1-hexanol, and the olefin product comprises 1-hexene.
52. (Currently Amended) The process of claim 37 wherein the halide-containing olefin oligomerization catalyst system ~~alkylaluminum compound~~ is a mixture of triethylaluminum and diethyl aluminum chloride, the alcohol is 2-ethyl-1-hexanol, and the olefin product comprises 1-hexene.
53. (Currently Amended) The process of ~~[[19]]~~ 18 wherein the olefin oligomerization product stream comprises one or more olefin trimers.
54. (Original) The process of 37 wherein the olefin oligomerization product stream comprises one or more olefin trimers.
55. (Currently Amended) The process of claim 37 wherein the halide-containing olefin oligomerization catalyst system comprises a halogenated alkylaluminum compound.
56. (Currently Amended) The process of claim ~~[[53]]~~ 55 wherein the halogenated alkylaluminum compound comprises diethylaluminum chloride.
57. (Currently Amended) A process to inhibit or limit the decomposition of a halide-containing olefin oligomerization catalyst system during recovery of ~~the-an olefin~~ olefin oligomerization product comprising the steps of:
- a) forming an intermediate stream by contacting an olefin oligomerization reactor effluent stream which comprises olefin product(s), catalyst system, and heavies with an alcohol that is soluble in any portion of the reactor effluent stream; and
  - b) separating the intermediate stream of step (a) into at least one olefin oligomerization product stream and at least one heavies stream;

33890US01  
10/800,471  
Art Unit: 1764

wherein the separation of step (b) comprises a distillation comprising a reboiler and material passed through the reboiler is maintained below about 190 °C, and

wherein the catalyst system comprises active metal alkyl units, and

wherein the alcohol is present in an amount greater than 0.1 and less than about 1.8 equivalents per equivalent of active metal alkyl units.

58. (Original) A 1-hexene stream produced by the process of claim 1.
59. (New) A 1-hexene stream produced by the process of claim 17.
60. (New) A 1-hexene stream produced by the process of claim 37.
61. (New) A 1-hexene stream produced by the process of claim 57.
62. (New) A process of claim 1, wherein the separation comprises at least two distillation stages and material passed through each reboiler is maintained below about 190°C.
63. (New) A process of claim 18, wherein the separation comprises at least two distillation stages and material passed through each reboiler is maintained below about 190°C.
64. (New) A process of claim 37, wherein the separation comprises at least two distillation stages and material passed through each reboiler is maintained below about 190°C.
65. (New) A process of claim 57, wherein the separation comprises at least two distillation stages and material passed through each reboiler is maintained below about 190°C.